

Appl. No. 09/754,264
Amendment and/or Response
Reply to Final Office Action of April 7, 2003

Page 3 of 9

Amendments to the Claims:

A clean version of the entire set of pending claims (including amendments to the claims, if any) is submitted herewith per 37 CFR 1.121(c) (3). This listing of claims will replace all prior versions, and listings, of claims in the application.

Listing of Claims:

10. (Previously Presented) A method of depositing a wiring thin film over a semiconductor substrate, the method comprising:

- providing a Al₃Ti target;
- providing a substrate;
- forming a Ti layer over said substrate;
- sputter depositing an Al₃Ti layer on said Ti layer using said Al₃Ti target; and annealing said substrate at a temperature of at least 400 °C to promote absorption of Si into said Al₃Ti layer.

11. (Previously Presented) A method as recited in claim 10, wherein an Al layer is deposited on said Al₃Ti layer.

12. (Previously Presented) A method as recited in claim 10, further comprising pattern-etching said Al layer thereby forming a wiring pattern.

13. (Previously Presented) A method as recited in claim 10, wherein the method further comprises forming an

Atty. Docket No. OKI.202

Appl. No. 09/754,264
Amendment and/or Response
Reply to Final Office Action of April 7, 2003

Page 4 of 9

insulating layer between said substrate and said Al,Ti layer.

14. (Previously Presented) A method of forming a wiring film, the method comprising:

- providing a substrate;
- depositing a Ti layer over said substrate;
- depositing an Al-Si-Cu layer on said Ti layer, which forms an Al,Ti on said Ti layer; and
- pattern etching an Al layer, which forms beneath said Al-Si-Cu layer.

15. (Previously Presented) A method as recited in claim 14, wherein said Al-Si-Cu layer is deposited at a temperature of at least 400 °C.

16. (Previously Presented) A method as recited in claim 14, wherein said substrate is annealed at a temperature of at least 400 °C.

17. (Previously Presented) A method of forming a wiring film, the method comprising:

- providing a substrate;
- depositing an Al,Ti layer over said substrate;
- depositing an Al layer on said Al,Ti layer; and
- pattern etching said Al layer.

18. (Previously Presented) A method as recited in claim 17, wherein said Al layer is deposited at a temperature of at least 400 °C.

19. (Previously Presented) A method as recited in claim 17, wherein said substrate is annealed at a temperature of at least 400 °C.

Atty. Docket No. OKI.202

Appl. No. 09/754,264
Amendment and/or Response
Reply to Final Office Action of April 7, 2003

Page 5 of 9

20. (Previously Presented) A method as recited in claim 17, wherein said Al₃Ti layer is deposited at a temperature of at least 400 °C.

Atty. Docket No. OKI.202

Received from <6103758380> at 8/7/03 10:16:17 PM [Eastern Daylight Time]